

HS-260 Acrylic 600 g/L Sealer Material Safety Data Sheet

Section 1: Product & Company Information

Product Name: HS-260

Manufacturer: SureCrete Design Products

Address: SureCrete Design Products

15246 Citrus Country Drive

Dade City, FL 33523

Service Used: Acrylic Cementitious Sealer

Application: Finishing Aid

Emergency Phone: 1-800-544-8488

CHEMTREC: 1-800-424-9300

INTERNATIONAL: 1-813-469-1408 INTERNATIONAL: 1-813-469-1419

Section 2: Ingredient Information			
•	Solvent Naptha (Petroleum), Light Aromatic 8-21% CAS# 64742-95-6 RCP-TWA 19 ppm / 100 mg/m³		
•	Xylene, mixed isomers 28-50% CAS# 1330-20-7 / TLV-TWA 100ppm / PEL-TWA 100ppm		
•	TertiaryButyl Acetate 4-16% CAS# 540-88-5 / TWA 100 ppm		

Isoocytl trimethoxysilane <9% CAS# 34396-03-7 / PEL 260 mg/m³, 200 ppm - TWA 200 ppm

Section 3: Physical/ Chemical Characteristics			
Boiling Point: 194-208°F	Specific Gravity (H ² O = 1): .91		
Vapor Pressure (mm Hg.): 1-3mm/Hg @ 20ºC	pH: 6 - 8		
Vapor Density (Air = 1) : 3.7 - 4.2	Evaporation Rate: slower than nBuAc		
Solubility in Water: negligible	Appearance and Odor: Clear liquid w/ characteristic odor		

Section 4: Fire and Explosion Hazard Data					
Flash Point: 49°F	Flammable Limits	LEL: 1.0	UEL: 10.0		
Extinguishing Media: Foam, CO2, Dry chemical					
Special Fire Fighting Procedures: Water may be ineffective in fighting fire. If water is used to cool containers, fog nozzles are preferred. Full protective equipment, including self-contained breathing apparatus required.					
Unusual Fire and Explosion Hazard: Overexposure to decomposition products may cause health hazard that is not readily apparent. Obtain medical attention.					

Section 5: Reactivity Data				
Stability: May be unstable under ambient conditions Conditions To Avoid: Heat, ignition sources				
Incompatibility (Materials to Avoid): Alkaline products, acids, oxidizers, reducing agents				
Hazardous Decomposition or Byproducts: oxides of carbon & various hydrocarbons				
Hazardous Polymerization: may occur				

Section 6: Health Hazard Data					
Route(s) of Entry:	Inhalation	Skin and Eye Contact	Ingestion		
Health Hazards (Acute and Chronic): May be irritating to skin, eyes, mucous membranes					
Carcinogenicity: suspected by IARC (Group 2B)					
Medical Conditions Generally Aggravated by Exposure: liver conditions, kidney conditions, neurological disorders, pregnancy, reproductive system disorders. Repeated overexposure can cause permanent brain and nervous system damage. Purposeful breathing of vapors can be fatal.					
	Emergency and Fi	rst Aid Procedures			
Inhalation: Move to fresh air. Administer artificial respiration if not breathing. If breathing is difficult, give oxygen. Get medical attention	Skin Contact: Wash affected area thoroughly with soap and water. Wash clothing before reuse.	Eye Contact: Rinse with running water for 15 mins hold eyelids apart while irrigating. Treat w/ Boric Acid solution	Ingestion: Get medical attention immediately.		

Section 7: Precautions for Safe Handling and Use Steps to Be Taken if Material is Released or Spilled: Remove all potential sources of ignition. Confine spill & reclaim as much product as possible with absorbent inert material. Waste Disposal Method: Dispose of in accordance with applicable federal, state, and local regulations. Precautions to Be Taken in Handling and Storage: Normal precautions according to good housekeeping practices should be followed. Other Precautions: Store in original containers, below 120°F.

Section 8: Control Measures					
Respiratory Protection: NIOSH approved respirator in enclosed area or when threshold levels are met.					
Ventilation					
Local Exhaust: Recommended	Mechanical (General): Recommended	Special: None known	Other: None		
Protective Gloves: Chemical Resistant Gloves Eye Protection: Safety goggles or face shield					
Other Protective Clothing or Equipment: Eyewash station / rubber apron					
Work / Hygienic Prac	tices: Normal good housekeeping	g practice			