

SUREFINISH



Toll Free 1-800-544-8488
Local 1-352-567-7973
www.SureCreteDesign.com

Technical Data

COVERAGE

1st coat:

approximately 1500 sq. ft per gal.

Subsequent coats:

2000-3000 sq. ft. per gal.

Packaging:

1 Gallon Jug or

5 Gallon Pail

Slip Resistance:

Classified by Underwriters Laboratories, Inc.® as to slip resistance only. 160S

DESCRIPTION

SureFinish beautifies and enhances resilient and non-resilient hard surface interior floors using any speed maintenance program. It is both easy to apply and maintain.

USE

SureFinish is specifically designed to provide superior protection for interior **SureCrete** Stamp Overlays and Chemical Stains that have been sealed with any of **SureCrete's** sealers. **SureFinish** will enhance the luster.

APPLICATION

After sealer has cured, SureFinish may be applied by mop. Protect the mop bucket with a trashcan liner to prevent contamination of **SureFinish**. The mop should be a closed loop mop head to prevent leaving "strings" in the finish product. Fully saturate the mop head and wring out so that mop is damp, but not dripping. Apply thin coats until desired initial gloss is achieved (usually 2-3 coats minimum). For optimum results burnish the first coat using a white or non-aggressive floor pad. Between coats allow the floor to dry to the touch and wait 15 additional minutes.

MAINTENANCE

Dust mop daily using an untreated mop head to remove loose dirt, dust, and soil. Wet mop to clean ground in soil as needed. Machine scrub heavily soiled areas and reapply thin coats of **SureFinish** as needed. Heavily trafficked areas may require monthly reapplication.