



Perma-Cast® Shake-on Color Hardener

Many things can affect the appearance of color. For best color matching results, a representative job site sample should be cast using materials from the project location.

Colors shown on this chart represent formulations using medium gray cement and sealed with solvent based Clear Guard® Cure and Seal. Variations can be expected due to differences in cement, aggregates and method of application.

 P41 Blue Stone	 P34 Nantucket White	 P20 Ginkgo	 P201 Travertine
 P11 Gray Plum	 P21 Coral Gables Pink	 P31 Gray Linen	 P32 Bone
 P29 Wheat	 P24 French Cream	 P22 Arena Buff	 P23 Smoke
 P28 Slate Gray	 P26 Cape Cod Gray	 P12 Storm Gray	 P13 Deep Charcoal
 P25 Colina Tan	 P14 Walnut	 P15 Brick Red	 P16 Dark Red
 P33 Juniper	 P17 Terra Cotta	 P18 Chestnut	 P19 Russet

Perma-Cast® Shake-on Color Hardener

Coloring System Guide



Scan for more information

625 W Illinois Ave, Aurora, IL 60506
800-282-3388 | www.butterfieldcolor.com

The Butterfield Color Advantage

Color is an integral part of what we see every day. From the subtle earthtones of sand, wheat, and sage, to the bright colors of a sunset or mountain range, combinations of colors can be used to set the mood and theme. Color decisions are made with two factors in mind – specific design needs and how well the color will endure year after year.

Color and durability are the very essence of Butterfield Color. With over 40 years of field experience in architectural colored concrete, we offer a line of concrete color additives that are technically superior and meet the needs of the architectural specifier as well as the concrete finisher.

FOR PROFESSIONAL USE ONLY

Read all applicable and current product information for your project: Technical Data Sheet (TDS), Color Chart, Installation Guide, Material Safety Data Sheet (MSDS).

MasterFormat™ Guide Specifications, and Butterfield Color® Architectural CAD Details and Hatch Patterns are available for the specifier/designer. All information is available online at: www.butterfieldcolor.com.

Description: Perma-Cast® Shake-on Color Hardener is a dry shake, color hardener that is applied to the surface of freshly placed concrete. It is a cementitious-based coloring material that may be used to create abrasion resistant interior floors and freeze-thaw stable exterior hardscapes. The time-tested formulation of Perma-Cast® Shake-on Color Hardener creates an extremely dense surface that is resistant to foot and vehicular traffic, and extreme weather. It is available in a wide range of streak free, uniform colors ranging from subtle pastels to deep, rich hues. It is used to uniformly color gray concrete, or provide random accents of color on concrete integrally colored with Uni-Mix® Integral Colorant, Uni-Mix® Liquid Integral Concrete Colorant or Select Grade™ Integral Concrete Colorant. Perma-Cast® Shake-on Color Hardener is also used when imprinting, texturing, or stenciling new concrete with Butterfield Color® Stamping Tools, Texture Rollers and Stencils. It is compatible with Clear Liquid Release, Perma-Cast® Antiquing Release and Select Grade™ Antiquing Release. Color hardened surfaces may also receive additional coloration by applying one or more colors of Perma-Cast® Sierra Stain™.

Perma-Cast® Shake-on Color Hardener is a precise blend of cement, silica quartz aggregates, synthetic metal oxides, and plasticizer. Perma-Cast® Shake-on Color Hardener conforms to ASTM Standard C979 for color stability. The water-reducing wetting agent in Perma-Cast® Shake-on Color Hardener allows it to be readily incorporated into the concrete surface, forming a rich paste that makes finishing easier. In addition to strength and durability, the color hardened surface is resistant to fading.

Perma-Cast® Shake-on Color Hardener is a pre-packaged material available in 24 standard colors. Custom colors, color matching, and colors selected from the Uni-Mix® Integral Colorant and Uni-Mix® Liquid color charts can be formulated with ample lead-time. Note: When a Perma-Cast® Shake-on Color Hardener is formulated from the Uni-Mix® Integral Colorant or Uni-Mix® Liquid color charts, the cured color will not be an exact match to the concrete colored with those integral coloring systems. Read all related or companion product Technical Data Sheets before installation.

Perma-Cast® Shake-on Color Hardener adds a wide array of color options to your architectural designs and hardscape projects while providing an extremely durable surface for pedestrian and vehicular traffic. Perma-Cast® Shake-on Color Hardener, used in conjunction with varying finishing techniques such as jointing schemes,

saw cutting and/or pattern stamping, can create a striking effect. Combinations of colors can be used to create a desired mood and theme. Perma-Cast® Shake-on Color Hardener is an excellent choice for high traffic industrial flooring, since it greatly increases the strength and durability of the concrete surface. Using lighter colors will optimize lighting in an industrial environment.

Limitations: Perma-Cast® Shake-on Color Hardener must be applied at the recommended broadcast rate. Review section 5 Coverage, of the Perma-Cast® Shake-on Color Hardener Technical Data Sheet. Applying insufficient material will reduce the abrasion resistance and may alter the color of the cured surface. Perma-Cast® Shake-on Color Hardener should not be mixed into ready mixed concrete nor applied onto cementitious overlays.

Perma-Cast® Shake-on Color Hardener is intended for application during new concrete flat-work installations. It may, however, be mixed with water and then plastered onto fresh vertical concrete such as step risers or curbs. Review section 8.4 Vertical Surfaces, of the Perma-Cast® Shake-on Color Hardener Technical Data Sheet, before Installation. Utilize concrete mix designs, tools, and techniques that ensure the thorough hydration of the material for proper finishing and curing.

Packaging: Perma-Cast® Shake-on Color Hardener is packaged in 50-pound (22.73 kg) plastic pails. Shelf life is 2 years from the date of invoice in original, unopened containers, in dry storage.

Quality Control: Cast a job site sample at least 21 days prior to the installation for approval of color and finish. Utilize all materials, tools, and techniques from the actual job in the mock-up. Consistent batching, pouring, finishing, curing, sealing, and preparation techniques, will ensure the uniformity of architectural concrete. Verify adequate wet and dry slip resistance. Verify maintenance requirements. Site visits by Butterfield Color, Inc. personnel are for making technical recommendations only and not for supervising or providing quality control.

LIMITED WARRANTY AND DISCLAIMER – EXCLUSIVE REMEDY: Butterfield Color, Inc. (“BC”) warrants that this product conforms to its published specifications when it is shipped. THIS LIMITED WARRANTY IS THE EXCLUSIVE WARRANTY AND THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. BC does not warrant any particular method of use or application of the product or its performance under any particular condition. If this product does not conform to its published specifications when shipped, we will replace the product as your exclusive remedy. Any action for breach of the limited warranty or any other liability arising from this product must be brought within 90 days of receiving the product. BC is not liable for consequential damages or personal injury arising from the use, storage or handling of this product.

FOR PROFESSIONAL USE ONLY

Before using or handling this product, read the entire:

- Perma-Cast® Shake-on Color Hardener Technical Data Sheet
- Perma-Cast® Shake-on Color Hardener MSDS
- Perma-Cast® Shake-on Color Hardener Directions for Use

For the most current documentation on this product visit us online at: www.butterfieldcolor.com

Cautions: Harmful if inhaled. This product contains silica (crystalline quartz) and Portland cement. Do not breathe dust. Prolonged exposure can result in Silicosis. Use with adequate ventilation. Portland cement may cause alkali burns. Irritating to eyes and skin. Wear a respirator, safety goggles, gloves, and other protective clothing during installation. Immediately after use, wash any area of exposed skin. If contact is made with the eyes, flush thoroughly with water, do not rub. Do not take internally. Keep out of reach of children and animals. Dispose of all residual materials according to local, state, and federal regulations. Slip resistant finishes, slip resistant additives must be utilized in order to minimize dry or wet slip. Read the Perma-Cast® Shake-on Color Hardener Material Safety Data Sheet (MSDS) and Technical Data Sheet (TDS) before installing the product.

Butterfield Color manufactures a complete line of quality **Decorative Concrete Products**.

Accept no substitutes for your project.

BUTTERFIELD
COLOR
Decorative
Concrete
COLOR
Quality Products backed by
unsurpassed Customer Support!

Distributed by: